

## **Fire Watch**

# Fire Watch - Dual Action Addressable Manual Pull Station



#### **Product Overview**

Product	Addressable Pull Station
Part No.	FW56000-005
Digital Communication	FW Protocol

### **Product Information**

The FW Dual-Action Addressable Manual Pull Station features a translucent plastic panel at the center enabling visibility of an internal LED that indicates polling and alarm status. For indoor use only.

The pull station may be flush mounted on a single-gang backbox of by using the optional backbox.

- Visible LED indicates polling and alarm status
- Key lock, easily reset
- Lightweight polycarbonate housing
- Optional backbox part no FW56000-006

### Technical Data

All specifications are subject to change without notice. Specifications are typical at 24 VDC, 73°F, and 50% RH unless otherwise stated.

Product Operating Temperature: 32 to 100°F Humidity: 10 to 95% RH, no condensation or icing

?

Dimensions: 4.13" W x 5.5" H x 1.14" D

Weight: 7 oz. (199 g)

Housing material: Red polycarbonate / ABS

Signaling Line Circuit (SLC): Supervised, Power Limited

Supply Voltage: 17 to 28 VDC Supervisory Current: 500 μA

Alarm Operated Current, LED ON: 1.6 mA per LED

Maximum Loop Current: 1A

# Operation

The address of each pull station is set at the commissioning stage by means of a seven-segment DIP-switch.

Pushing in and then pulling down on the handle causes it to latch in the down/activated position.

Once activated the yellow activated flag appears at the bottom of the panel station face. The pull station is reset by inserting and turning the reset key into the top of the unit. This opens the door of the pull station allowing the handle to return to the normal position. Closing the door automatically resets the switch.



# **Fire Watch**

# FIREWATCH - Manual Pull Station Backbox



## **Product Overview**

Product PullI Station Backbox

Part No. FW56000-006

### **Product Information**

The FW Manual Pull Station Backbox is used to allow surface mounting of the FW Manual Pull Station

### **Technical Data**

All specifications are subject to change without notice.

Color: Red Weight: 88 g

Length: 5.51" (140 mm) Width: 4.25" (108 mm) Depth: 1.77" (45 mm) Warranty: 10 years